

SAVOX® C-C500

multi-purpose remote speaker mic



User data

- can be used with or without a headset
- adapts any SAVOX headset to your two-way radio
- two large push-to-talk buttons
- durable and water-resistant (IP 67)
- rotating belt clip
- ergonomic
- optimal size



TECHNICAL DATA

| | |
|------------------------------|--|
| Weight | 200 g |
| Size | 110 x 65 x 25 mm |
| Cable | Ø 4 mm, PU, length according to application |
| Microphone | omnidirectional electret |
| Speaker impedance | 8 ohm @ 1kHz |
| Speaker/ mic cable | Ø 2.5 mm, 290 mm/195 mm (PVC/PUR) |
| Connectors | 4-pole quick-release jack/radio-specific connector |
| Operation temperature | -25 to +63 °C (continuous) |
| Supply voltage | 2,5–10,0 VDC |
| Humidity | 95% RH, +63 °C for 500 hours |
| Ingress protection | IP67 |
| ESD, EMI immunity | conforms to EN 301 489-1 |

OPTIONS

- remote PTT
- function buttons



SIGMACOM
radiocommunication.ch

Rue de la Dixence 49 – CH-1950 Sion
T +41 (0)27 322 41 01 F +41 (0)27 322 41 02
info@sigmacom.ch – www.sigmacom.ch